



# USER GUIDE


FOR RA708 SERIES  
WEATHER RESISTANT TELEPHONES

# GENERAL

*The RA708 type weatherproof telephone from DAC Limited is designed to provide a reliable communications terminal for many arduous communications applications.*


The telephone can be connected as an extension, on most types of PBX [see details under 'line connections'] or via a standard BT telephone socket.

## MOUNTING OPTIONS




### Wall Mounting

Use reducing washers [supplied as part of installation kit] to affix to wall through telephone backplate.



### Top of Pole Mounting

Top of pole mounting bracket available from DAC Limited



### Pole or Post Mounting


Use pole mounting adaptor bracket [supplied as part of installation kit] and band at required height on pole

# LINE CONNECTION

The number of telephones that can be connected to a direct exchange line PBX is limited to the ringer equivalence number [REN] of all the telephones connected, which should not exceed a total value of 4. The REN value of this telephone is 1. In case of doubt please contact your telephone supplier. ***The following information is provided for use by your approved telephone installer or network supplier.***


## Terminal Connections

B - Line [B]  
A - Line [A]



## Earth Bonding

The earth bonding point is on the rear of the telephone.



**Available options:**

- 1      Armoured Cord Handset
- 2      Padlock Hole in door
- 3      Latching Door
- 4      Telephone logo
- 5      Installation kit
- 6      Top of pole mounting kit
- 7      Yellow or Grey colour

**Distributor:**

DAC Limited, Unit 28 Lomeshaye Business Village, Turner Road   
Nelson, Lancashire. UK. BB9 7DR

Tel: +44 (0) 1282 447000 Fax: +44 (0) 845 280 1915

[www.daclimited.co.uk](http://www.daclimited.co.uk)